



Specifications:

Model	GRABO H / NGH-V2
Battery	7.4
Rated Power	10 W
Rated Air Flow	7 L / min
Dimensions	10.94x6.38x4.72(in) / 278x162x120 (mm)
Maximum Vacuum Rate	-0.8 Bar (-80 kPa)
Maximum Lifting Capacity	330 lbs (150 kgs)
Charger Input Voltage	100 - 240 VAC 50 / 60 Hz
Running Cycles (On Full Charge)	340 ON - OFF cycles 10 seconds
Stand By Mode (Full Charge)	25 Days
Pump Service Life	100000+ ON - OFF Cycles 800+ Hours
Net Weight (With Battery)	2.6 lbs (1.2 kgs)
Working Temperature	32 F ~ 120 F (0 C ~ 60 C)
Applicable Surfaces	Peak - Valley Heights Less Than 0.1" (3mm) Arc Less Than 5 degrees.

Lifting Capacity:

Material \ Direction	Glass	Ceramic Tiles	Metal	Plastic	Wood	Rough Slate	Rough Concrete	Dry Wall
Perpendicular Hold 	330Lbs (150 kg)	330Lbs (150 kg)	242Lbs (110 kg)	220Lbs (100 kg)	176Lbs (80 kg)	176Lbs (80 kg)	176Lbs (80 kg)	132Lbs (60 kg)
Parallel Hold 	220Lbs (100 kg)	220Lbs (100 kg)	176Lbs (80 kg)	176Lbs (80 kg)	132Lbs (60 kg)	132Lbs (60 kg)	132Lbs (60 kg)	88Lbs (40 kg)

GRABO headquarters:

Eastern Commerce Center
6000 S Eastern Ave
Suite 9E
Las Vegas, Nevada, 89119

Info@GRABO.com

www.GRABO.com

Main Office:

+1 (844) 430-0510

Help & Warranty:

+1 (702) 718-2433

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product manual on GRABO.com or contact a Sales Representative for more information.

By Nemo Power Tools - www.GRABO.com