



GREAT TOP

This product was especially developed to harden the surface of all kind of marble, granite, agglomerate, quartzite etc. “GREAT TOP” can excellent deep penetration into the stone surface and fill the small hole on the surface of stone. It can also reduces detrition and wear. Subsequent surface treatments such as impregnation etc. are possible. “GREAT TOP” considerably increases the quality and the value of natural stone.

FUNCTIONS Water-based liquid

INDICATIONS

1. Deep penetrate to harden the surface of all kinds of stone. Reduce early detrition and wear of stone.
2. Base on Moh's Hardness Scale, the surfaced (limestone or marble) treated with Great Top will be increased 2 of hardness.

MATERIALS Suitable for all types of marble, granite, agglomerate, quartzite stone etc

USAGE

1. The surface to be treated must be dry, free of grease and clean. Previous chemical treatment of the stone surface can reduce or even prevent the hardening process.
2. The undiluted product is applied with paint brush. The surface must be dry, free of grease and clean. The product needs 30 to 45 minutes to penetrate into the surface of the stone and to harden.
3. Clean floor with a diluted solution of ITALCINA Neutrex detergent using a scrubbing machine and a red buffing pad. Then, the treated surface is walkable. And you can apply crystallizing product for a durable high gloss shining.
4. Approx. 1 liter for 5 to 8 square meters, depending on the treated surface

NOTES

1. Not Flammable!
2. Provide for good ventilation during and after the use of the product. Keep the product inaccessible for children. Once the product has hardened, it does not cause any risk to the human health
3. Keep the product closed, cool and dry.
4. Stone floorings that had been hardened with “GREAT TOP” may only be cleaned with PH-neutral cleaning agents.
5. A preliminary test on a small part of the surface is suggested.