



PROOF 10S plus

Solvent based product with excellent deep penetration into stone surfaces, even with low porosity, penetrating deep for a significant “anti-infiltration” effect. Does not noticeably change the surface appearance and the main physical and mechanical characteristics (hardness, conductivity, compression resistance, abrasion etc.) Of the treated materials and leaves the stone’s natural transpiration action (vapour permeability) intact. Once the solvents are evaporated, the food can safely come in contact with the surfaces without any risk to human health. The substances found in PROOF 10S PLUS are safe for preparation areas.

FUNCTIONS Oil and water repellent, anti-infiltrant, anti-stain, polymer impregnator. Protects the treated surfaces from external agents while preserving the natural properties of the stone (such as colour and transpiration ability)

PRODUCT LINE PROTECTION PROFESSIONAL

INDICATIONS Protects against water, oil and grease: makes the surface stain resistant by preventing the formation of spots. It doesn’t anyway protect against acid substances.

MATERIALS Recommended for all types of porous surfaces unfinished, polished, hammered-rough, flashed of marble, granite, natural stone, cement, limestone, terrazzo, slate, wallcovering, travertine roof tiles, flowers pots etc.

HOW TO USE Apply the undiluted product to clean, dry and free from greasy substances surfaces and allow to penetrate. Spread the product on area to be treated with clean cloth or brush so that product uniformly covers surface, but avoiding that excess of product dries on the surface. For very porous materials, it may be necessary to repeat the procedure after the surface has dried.

TEST Testing a small, hidden area is recommended before application to determine compatibility between product and material, consumption, drying time and to verify appearance.

COMPOSITION Contains organic polymers and solvents

TECHNICAL INFORMATION Dries in 10 to 20 minutes, depending on the absorption level of the treated surface, the quantity of product applied and climatic conditions (temperature, relative humidity, ventilation etc.). The protection effect is fully operative after 24 hours from the last application.

LIMITATION OF LIABILITY The data provided derive from published information or from our own laboratory tests. The information provided here should be considered as a guideline and not as any form of performance guarantee. Liability for defective products, when verified, is limited to the refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier

NOTE Solvent-based product: apply in well ventilated areas while wearing impermeable gloves. For more information, see product label or product Safety Data Sheet.

IMPORTANT Apply to completely dry and clean surface. Do not apply on surfaces sensitive to the solvents. In case of doubt effect always a preliminary test.