



TECHNICAL DATA SHEET  
PRODUCT

**S35**  
**STONE SEALER**

**Recommend for non-polished surface**

**S35** Stone Sealer is a modified silicone/acrylic base sealer, which produces a tough, hard, and highly protective finish. **S35** protects against water, dirt, and oil infiltration. For interior and conditional exterior use on honed, flamed and textured mineral surface. **S35** enhances the stone's color and texture, while leaving a matt finish. **S35** is highly vapour permeable, UV resistant, and slip retardant. **S35** builds up a tough, hard matt finish and does not yellow or cloud due to ultraviolet, and keeps its natural appearance. Do not use in wet areas or on polished, glazed or non-absorbing surface.

<b>FUNCTION</b>	Solvent based product for protection
<b>INDICATION</b>	Makes the treated surfaces waterproofing and anti-dirt.
<b>MATERIALS</b>	All absorbent non-polished natural stone, marble, granite, concrete, travertine, etc.
<b>USAGE</b>	<ol style="list-style-type: none"><li>1. Apply to chemically clean and dry surface with brush or roller. One or two thin and even applications are usually sufficient, depending on the porosity of the stone and desired color enhancement.</li><li>2. Allow 30-90 minutes between each application, do not allow to bubble.</li><li>3. Allow 24-48 hours fully cure before walking.</li><li>4. Consumption will be vary greatly depending on the porosity of materials, the coverage is between 6-10 sq.m per liter.</li></ol>
<b>NOTES</b>	<ol style="list-style-type: none"><li>1. S35 is solvent-based product and should only be applied in well-ventilated area while wearing waterproof gloves. Keep out of the reach of the children.</li><li>2. A preliminary test on a small part of the surface is suggested.</li></ol>