



TECHNICAL DATA SHEET  
PRODUCT

**AGGLOPOLISH B1  
PREMIER**

**SPECIAL POLISHING POWDER  
for MARBLE AGGLOMERATES  
(synthetic marbles) of medium hardness**

**SPECIAL POLISHING FORMULATION IN POWDER CONTAINING NATURAL RESINS**

Thanks to the use of high-level abrasive substances combined with sealant, synthetic and crystallizing chemical substances, AGGLOPOLISH B1 PREMIER performs a perfect chemical-mechanical polish on marble agglomerates.

The granular dimensions have been exhaustively researched, formulated and balanced with abrasive grains consisting of base crystals of medium/high hardness to allow a fastest and most economical mechanical polishing on marble agglomerates of medium hardness and to obtain a glossy stable during the time.

AGGLOPOLISH B1 PREMIER performs a "filling" function of the micro-cavities on the surface for a higher shine.

**HOW TO USE**

Carefully clean the surface and remove any kind of dirt and solid residuals. Apply 30 to 60 grams of product per square meter (abt. 1-2 tablespoons) and dampen the area by spraying water till to obtain a milky/creamy consistency.

Put the felt/pad of the traditional polishing machine or single-brush machine on the milky/creamy mixture and polish with continuous and constant motion. Work 1-2 square meters time by time for a more homogeneous polishing.

Friction will cause the water evaporation so, eventually, spray water to maintain the product creamy. With the drying the marble becomes shining.

Verify the glossy effect with a window-wiper by removing the surface patina. On the surface will remain a light patina of product; on a small area use a cloth to remove the surface patina and check the level of gloss underneath and, if necessary, repeat the operation. Once the polishing phase is completed on the entire surface to be treated, remove the residual patina by washing with **Neutrex** diluted in a 1:5 water solution. Rinse with clear water.

**IMPORTANT**

The best results are obtained by using a professional buffing machine able to produce significant friction, but very good results are obtained also with a common single-brush polishing machine that are particularly suitable for restoring and renewing the glossy of old floors or floors became dull because of high pedestrian traffic and wear and tear.

The shine duration strictly depends on the wear and tear of the floor. For a longer life of the shine a light application of wax is suggested; that should be regularly applied during the floor scheduled maintenance.

Effect a preliminary test on a small part of the surface to calculate consumption and measuring according to the kind of material and to verify, after drying, that no polishing halos or marks are on the surface; in this case a test with *AGGLOPOLISH B2 EXTRA* is suggested.

For marble agglomerates of low hardness or soft or of light colours the use of *AGGLOPOLISH B2 EXTRA* is suggested.

**LIMITATION OF LIABILITY**

The data provided derive from published information or from our own laboratory tests. The information provided here must be considered as a guideline and not as any form of performance guarantee.

Liability for defective products, when verified, is limited to refund of the purchase price since application of the product is beyond the control of the manufacturer or supplier.

**A TEST IN A SMALL, HIDDEN, AREA IS ALWAYS RECOMMENDED BEFORE THE APPLICATION**