



Gres GP

Stain and dirt protector for stoneware

DESCRIPTION

Gres GP is a revolutionary new system that protects stoneware surfaces. Thanks to its innovative formula, Gres GP penetrates through the micro-porosities on the surface and filling them eventually eliminating the pores! It protects the treated surface without creating an unattractive film and ensures ultra high resistance to foot traffic dirt.

- ▶ **Excellent performance**
- ▶ **Resistance to foot traffic**
- ▶ **Resistance to daily cleaning**
- ▶ **Ideal for internal and external use**
- ▶ **High resistance to UV rays without yellowing effect**
- ▶ **Easy to apply**
- ▶ **Anti stain**
- ▶ **Does not create unattractive and sliding films**

DIRECTIONS:

AFTER LAYING: If the tiles have just been laid, wash with KALGRES or GRESAL (FC02), a mild acid cleaner, to remove any cement residues.

MAINTENANCE: If the surface is not new, wash with CLEAN SPECIAL or DEGREASER (FC03)

If the tiles are very dirty, revitalize them with GRES UP (FC05).

On perfectly clean and dry surfaces, apply uniformly one coat of the product using a brush, a soft cloth or any other suitable applicator, taking care to treat a few meters (2-4 mq) at a time and to apply the product both on the tiles and on the joints.

After some minutes finish the dry surface with an electric Mono brush equipped with white pad.

The Floor can be open to light foot traffic after 12-24 hours.

The second coat can be applied after 2-4 hours or when the surface is completely dried.

Rub the treated surface with a white cotton cloth or with mono brush with a white pad.

Remove any excess product within 20 minutes of applying using an electric Mono brush equipped with a white pad or a white cotton cloth.

The complete reticulation takes 48 hours.

PERFORMANCE:

Approx. 40/60 m²/L



GRES GP 瓷磚高效防污劑

GRES GP是革命性瓷磚防污劑，滲透並填充到表面的微孔中，最終消除瓷磚表面的毛孔，在瓷磚上形成保護，有效抵抗污漬及抗高人流。減少日常清潔，抗紫外光，不會發黃。操作簡單，效果美觀，處理過的表面，不會產生薄膜，也不會影響表面防滑。

優點:

- 高效能
- 抗高人流
- 耐日常清潔
- 可室內外使用
- 抗紫外光，不發黃
- 操作簡單
- 防污
- 美觀，不會影響防滑

使用方法:

1. 將處理面清潔乾潔
2. 用油刷將產品均勻塗在處理面和縫隙位置
3. 幾分鐘後，用白色墊擦乾表面
4. 12-24小時後表面可供人流行走
5. 第二層施工可在表面乾透後或第一次塗完後2-4小時處理
6. 用白色墊在處理後20分鐘內將多餘的殘留物清除
7. 48小時後可全面性保護

使用面積:

40/60平方米/公升